

Reactor and process for carrying out heterogeneous catalytic reactions.

Publication number: EP0534195

Publication date: 1993-03-31

Inventor: RUPPEL WILHELM DR (DE); THOMAS HANS-RICHARD DR (DE); BOECK STEFAN DR (DE); HERZOG KLAUS DR (DE); RESCH PETER DR (DE); PLUECKHAN JUERGEN DR (DE); MROSS WOLF DIETER DR (DE)

Applicant: BASF AG (DE)

Classification:





- international: *B01J8/00; B01J8/02; C07C51/235; C07C57/055; C07D301/08; C07D303/04; B01J8/00; B01J8/02; C07C51/16; C07C57/00; C07D301/00; C07D303/00; (IPC1-7): B01J8/02*

- European: B01J8/02B2; B01J8/02H


Application number: EP19920115129 19920904

Priority number(s): DE19914131446 19910921

Also published as:

 JP5261272 (A)
 DE4131446 (A1)
 EP0534195 (B1)
 ES2075552T (T3)

Cited documents:


 GB2046618
 US2363738

[Report a data error here](#)

Abstract of EP0534195

The application relates to a reactor and a process for carrying out heterogenous catalytic gas-phase reactions. The process is characterised in that the reaction mixture flows through a loose catalyst bed (01) radially with respect to the longitudinal axis of the reactor and preferably in a centripetal direction. A further characteristic of the process according to the invention is the incorporation, in the catalyst bed (01), of a heat exchanger (02) having coiled tubes (03) which have a heat transfer medium flowing through them to remove the reaction heat liberated.

FIG.2



.....
Data supplied from the *esp@cenet* database - Worldwide